

TITAN

Titan Emergency Exit 24m

- Single and double sided decals
- Fully compliant (AS/NZS 2293)
- Wall, ceiling, chain mounting
- · Long life electronics
- High Quality Lithium battery (LiFePO4) and smart charger
- Standalone (SPU)









SPECIFICATIONS	
Brand	Alchemy
Illumination	Legend: Long-life, high-intensity LEDs
Housing	Injection-molded thermoplastic ABS
Legend	2 Middle, 1 Left/Right exit decals
Input Voltage	220-240VAC 50Hz
Input Rating	4.0W
Battery	Maintenance-free 3.2V LiFePO4 battery
Operating Temperature	0°C to 40°C
Charging Time	24 hours
Discharge Time	180 minutes
Mounting	Wall and ceiling
Ingress Protection	IP20
Electrical Rating	Class II
Viewing Distance	24m
Finish	White
IK Rating	N/A
Emergency Rating	C0: D12.5 C90: D8
Testing Method	Manual Test Switch
CRI	>80
Lifetime Expectancy	50,000 Hrs
Luminous flux	106.72lm

Brand	Alchemy
Illumination	Legend: Long-life, high-intensity LEDs
Housing	Injection-molded thermoplastic ABS
Legend	2 Middle, 1 Left/Right exit decals
Input Voltage	220-240VAC 50Hz
Input Rating	4.0W
Battery	Maintenance-free 3.2V LiFePO4 battery
Operating Temperature	0°C to 40°C
Charging Time	24 hours
Discharge Time	180 minutes
Mounting	Wall and ceiling
Ingress Protection	IP20
Electrical Rating	Class II
Viewing Distance	24m
Finish	White
IK Rating	N/A
Emergency Rating	C0: D12.5 C90: D8
Testing Method	Manual Test Switch
CRI	>80

INSTALLATION	
BATTERY	Please make sure to connect battery before first use.

ORDERING INFORMATION	
Barcode	0726436717007
Description	Titan emergency Exit
Item Code	AL8EM-TITAN

	PRODUCT / PACKAGE / WEIGHT	
	Product (mm) Weight (kg)	333.2 x 209.6 x 78.8 (0.8kg)
Outer Carton Quantity 10	Outer Carton (cm) Weight (kg)	47.5 X 35.5 X 45 (11.80kg)
	Outer Carton Quantity	10

COMPLIANCE	
Standards	AS/NZS 60598.1 AS 60598.2.22 AS/NZS 61347.1 AS/NZS 61347.2.13 AS CISPR 15 AS/NZS 2293.3

WARRANTY	
Replacement Warranty	3 Years Return to base
Labour not included	2 Years Battery
	<u> </u>

LINE DRAWINGS

AL8EM-TITAN





80 mm