

## **MONARCH**

Monarch Slimline Emergency Exit 24m

- Slimline Exit Light
- 3.2V LiFePO4 (Lithium) Battery
- 3 Years Warranty
- Single/Double Sided
- Viewing Distance: 24M









Brand Alchemy  Illumination Legend: Long-life, high-intensity LEDs  Housing Injection-molded ABS housing  Legend 2 Middle, 1 Left/Right exit decals  Input Voltage 220-240VAC 50Hz  Input Rating 2.5W  Battery Maintenance-free 3.2V LiFePO4 battery  Operating Temperature 0°C to 40°C  Charging Time 24 hours  Discharge Time 180 minutes  Mounting Wall/Ceiling (Optional Suspension Kit)  Ingress Protection IP20  Electrical Rating Class II  Viewing Distance 24  Finish White  IK Rating N/A  Emergency Rating C0: D12.5 C90: D8  Testing Method Manual Test Switch  CRI >80  Luminous flux 114 92 lpm	SPECIFICATIONS	
Housing	Brand	Alchemy
Legend         2 Middle, 1 Left/Right exit decals           Input Voltage         220-240VAC 50Hz           Input Rating         2.5W           Battery         Maintenance-free 3.2V LiFePO4 battery           Operating Temperature         0°C to 40°C           Charging Time         24 hours           Discharge Time         180 minutes           Mounting         Wall/Ceiling (Optional Suspension Kit)           Ingress Protection         IP20           Electrical Rating         Class II           Viewing Distance         24           Finish         White           IK Rating         N/A           Emergency Rating         C0: D12.5 C90: D8           Testing Method         Manual Test Switch           CRI         >80           Lifetime Expectancy         50,000 Hrs	Illumination	Legend: Long-life, high-intensity LEDs
Input Voltage         220-240VAC 50Hz           Input Rating         2.5W           Battery         Maintenance-free 3.2V LiFePO4 battery           Operating Temperature         0°C to 40°C           Charging Time         24 hours           Discharge Time         180 minutes           Mounting         Wall/Ceiling (Optional Suspension Kit)           Ingress Protection         IP20           Electrical Rating         Class II           Viewing Distance         24           Finish         White           IK Rating         N/A           Emergency Rating         C0: D12.5 C90: D8           Testing Method         Manual Test Switch           CRI         >80           Lifetime Expectancy         50,000 Hrs	Housing	Injection-molded ABS housing
Input Rating   2.5W	Legend	2 Middle, 1 Left/Right exit decals
Battery Maintenance-free 3.2V LiFePO4 battery Operating Temperature 0°C to 40°C Charging Time 24 hours Discharge Time 180 minutes Mounting Wall/Ceiling (Optional Suspension Kit) Ingress Protection IP20 Electrical Rating Class II Viewing Distance 24 Finish White IK Rating N/A Emergency Rating C0: D12.5 C90: D8 Testing Method Manual Test Switch CRI >80 Lifetime Expectancy 50,000 Hrs	Input Voltage	220-240VAC 50Hz
Operating Temperature         0°C to 40°C           Charging Time         24 hours           Discharge Time         180 minutes           Mounting         Wall/Ceiling (Optional Suspension Kit)           Ingress Protection         IP20           Electrical Rating         Class II           Viewing Distance         24           Finish         White           IK Rating         N/A           Emergency Rating         C0: D12.5 C90: D8           Testing Method         Manual Test Switch           CRI         >80           Lifetime Expectancy         50,000 Hrs	Input Rating	2.5W
Charging Time         24 hours           Discharge Time         180 minutes           Mounting         Wall/Ceiling (Optional Suspension Kit)           Ingress Protection         IP20           Electrical Rating         Class II           Viewing Distance         24           Finish         White           IK Rating         N/A           Emergency Rating         C0: D12.5 C90: D8           Testing Method         Manual Test Switch           CRI         >80           Lifetime Expectancy         50,000 Hrs	Battery	Maintenance-free 3.2V LiFePO4 battery
Discharge Time         180 minutes           Mounting         Wall/Ceiling (Optional Suspension Kit)           Ingress Protection         IP20           Electrical Rating         Class II           Viewing Distance         24           Finish         White           IK Rating         N/A           Emergency Rating         C0: D12.5 C90: D8           Testing Method         Manual Test Switch           CRI         >80           Lifetime Expectancy         50,000 Hrs	Operating Temperature	0°C to 40°C
Mounting   Wall/Ceiling (Optional Suspension Kit)	Charging Time	24 hours
Ingress Protection         IP20           Electrical Rating         Class II           Viewing Distance         24           Finish         White           IK Rating         N/A           Emergency Rating         C0: D12.5 C90: D8           Testing Method         Manual Test Switch           CRI         >80           Lifetime Expectancy         50,000 Hrs	Discharge Time	180 minutes
Class   I	Mounting	Wall/Ceiling (Optional Suspension Kit)
Viewing Distance         24           Finish         White           IK Rating         N/A           Emergency Rating         C0: D12.5 C90: D8           Testing Method         Manual Test Switch           CRI         >80           Lifetime Expectancy         50,000 Hrs	Ingress Protection	IP20
Finish         White           IK Rating         N/A           Emergency Rating         C0: D12.5 C90: D8           Testing Method         Manual Test Switch           CRI         >80           Lifetime Expectancy         50,000 Hrs	Electrical Rating	Class II
IK Rating	Viewing Distance	24
Emergency Rating         C0: D12.5 C90: D8           Testing Method         Manual Test Switch           CRI         >80           Lifetime Expectancy         50,000 Hrs	Finish	White
Testing Method         Manual Test Switch           CRI         >80           Lifetime Expectancy         50,000 Hrs	IK Rating	N/A
CRI >80  Lifetime Expectancy 50,000 Hrs	Emergency Rating	C0: D12.5 C90: D8
Lifetime Expectancy 50,000 Hrs	Testing Method	Manual Test Switch
	CRI	>80
Luminous flux 114 03lm	Lifetime Expectancy	50,000 Hrs
Luminous nux	Luminous flux	114.93lm

ORDERING INFORMATION	
Barcode	0726436717090
Description	Monarch Emergency Exit
Item Code	AL8EM-MONARCH

PRODUCT & PACKAGE	
Product (mm) Weight (kg)	370 x 210.7 x 90 (0.74kg)
Outer Carton (cm) Weight (kg)	44 x 32.5 x 27 (7.4kg)
Outer Carton Quantity	10

COMPLIANCE		
Standards	AS/NZS 60598 AS/NZS 61347 AS CISPR 15 AS/NZS 2293	

WARRANTY	
Replacement Warranty	3 Years Return to base
Labour not included	2 Years Battery
INSTALLATION	
	_, ,

INSTALLATION	
BATTERY	Please make sure to connect battery before first use.

## OPTIONAL

## AL8EM-SKMONARCH



Ceiling Mounting Suspension Kit 550mm

## LINE DRAWINGS

AL8EM-MONARCH

