



Surface Blade 24m

AL8EM-BLADE-SM

- Viewing distance 24m, double sided
- SAA and AS/NZS2293 Classification: C0/D3.2,C90/D2
- Surface ceiling Mounted Quick Mount Bracket



SPECIFICATIONS

Brand	Alchemy VIII
Illumination	Bridgelux High Lumen SMD2835
Housing	Injection-molded ABS housing
Legend	2 Middle, 1 Left/Right exit decals
Input Voltage	220-240VAC 50Hz
Input Rating	4W
Battery	Maintenance-free 3.2V LiFePO4 battery
Operating Temperature	0° to 50° C
Charging Time	24 hours
Discharge Time	180 minutes
Mounting	Wall/Ceiling (Optional Suspension Kit)
Ingress Protection	IP20
Electrical Rating	Class II
Viewing Distance	24
Finish	White
IK Rating	N/A
Emergency Rating	C0/D5 ,C90/D2 .5
Testing Method	Manual Test Switch
CRI	>80
Lifetime Expectancy	50,000 Hrs
Luminous flux	114.93lm

ORDERING INFORMATION

Barcode	-
Description	Surface Mount Blade 24m
Item Code	AL8EM-BLADE-SM

PRODUCT & PACKAGE

Product (mm) Weight (kg)	392mm x 85mm x 244mm 0.6Kg
Outer Carton (cm) Weight (kg)	44 x 38.5 x 40 (9.4kg)
Outer Carton Quantity	10

COMPLIANCE

Standards	IEC 60598-1:2014+A1:2017 IEC 60598-2-22:2014+A1:2017 IEC60570:2003+A1/A2:2019 AS/NZS60598.1/A1/A2:2020 AS 60598.2.22:2019 AS/NZS 2293.3:2018/A1:2021
-----------	---

WARRANTY

Replacement Warranty	3 Years Return to base
Labour not included	2 Years Battery

INSTALLATION

BATTERY Please make sure to connect battery before first use.

LINE DRAWINGS

